

## Cool Top Trail 28V/36V Variable Speed Compressor



Webasto RV Air Conditioners enhanced with advanced Variable Speed Compressor Technology offer exceptional cooling capacity, low noise levels, and a stylish low-profile streamline design.

Made using UV stabilised polypropylene, these air conditioners are robust and lightweight, ensuring long-lasting performance without adding unnecessary weight to your caravan.

Webasto Air Conditioners provide powerful cooling and heating capacity while consuming less energy. Thanks to the smooth start-up feature, you won't experience any starting peaks that might strain your power supply. The Eco mode further reduces electrical power consumption, optimising energy usage without compromising on comfort and turbo mode allows for rapid cooldown or heat-up.

With the easy-to-handle remote control, you can effortlessly switch between heating, cooling, dry, sleep, timer, turbo and Eco functions. These functions enable the air-conditioning system to operate effectively in extreme temperatures, from as low as -5°C to as high as 50°C.

Webasto Air Conditioners have excellent reverse cycle performance and are supplied with a 3 year Australia wide warranty and on-going technical support.

## **Features and Benefits**

- 220-240 V
- Cooling Capacity from 2800 W up to 3600 W
- Turbo mode for fast cool down or heat up
- Low profile, slimline design
- Low noise
- High quality variable speed compressor and components
- Operates in temperatures as low as -5°C and as high as 50°C.
- Remote control to select heating, cooling, dry, sleep and timer functions
- Eco Modes reduce power consumption
- Reverse cycle air-conditioner with a four speed fan
- Patented spiral retractable duct for easy installation
- Easy to remove & clean Air filter
- Strong and lightweight UV stabilised cover designed to withstand the toughest conditions
- 3 year Australia wide warranty

## **RV Air-Conditioning System**



























## **Technical Specifications**

	Cool Top Trail 28V	Cool Top Trail 36V
Nominal Voltage (V) / Frequency (Hz)	220-240 / 50	220-240 / 50
Rating Cooling (kW)	2.8	3.6
Rated Heating (kW)	2.6	3.3
Rated Current Cooling / Heating / Max (A)	4.8 / 4.8 / 5.8	6.4 / 6.2 / 7.4
Unit Net Weight Outdoor (kg)	31.9	38.9
Unit Net Weight Indoor (kg)	3	3
Operating Temperature Range (°C)	-5 to 50	-5 to 50
Roof Thickness (mm)	25 to 70	25 to 70
Rooftop Cut-out (mm) - Options	360 x 360 or 400 x 400	360 x 360 or 400 x 400
Dimensions Outdoor (L x W x H mm)	855 x 657 x 215	1122 x 850 x 223
Dimensions Indoor (L x W x H mm)	575 x 556 x 49	575 x 556 x 49